Specifications of Equipment for Tender Bid cum Quotation

Name of Equipment/ Assembly	Long Term Flow Test Apparatus
Related Standards to be accorded	IS 16389, ASTM D4716
Features/capabilities /Specifications	 Equipment shall be separated in upper and lower tube and have space to house the Specimen inside with 100 mm clearance on both sides. Specimen diameter shall be 100 mm. Capable of adjustment of Head loss at least 50 mm. Liquid collected from the discharge tube to flow rate shall be readable in ml/min Overhead tank of size 100 L
Make	Clear mention Make in the bid
Electrical Supply Requirement	 Electricity supply requirements (voltage and phase) shall be clearly mentioned Mention in case of Requirement of UPS (Uninterrupted Power Supply) with capacity
Size and weight	 Mention area required for positioning of equipment. Mention total weight of the equipment. Mention specific requirement of foundation/pedestal for resting the equipment, if any. Mentioned need of vibration isolated, if needed
Water and air supply requirements Compatibility of parts	 Mention the requirement to supply of compressed air, if any. Mention the requirement and arrangement of water supply, if any. In case of accessories from make differing to the make of equipment, compatibility shall be checked and certified by the bidder.
Calibration Certificates, technical manual and SOP	 The calibration certificates shall be provided with equipment and accessories. Validity of calibration certificate for all devises shall not be less than one year. Technical manual and Standard Operating Procedure document shall be provided.